



THE FOLLOWING SPECIFICATIONS ARE FOR A STANDARD ROLL-OFF PUP TRAILER

STANDARD SPECIFICATIONS

TYPE

REEVING UNIT, FULL TILT FRAME ROLL-OFF CHASSIS

RATED CAPACITY

120,000# CYLINDER CAPACITY, 30,000# LINE PULL

CONTAINER CAPACITY

UP TO 24" (LARGER AVAILABLE)

RAIL SIZE

- RECTANGULAR TUBING 12" X 4" X 3/8"
- LENGTH APPROXIMATELY 26'

RAIL WIDTH

STANDARD SPACING IS 34"

FRAME

3/8 T-1 X 11' CHANNEL

TILT ANGLE

46 DEGREES (APPROXIMATE)

AXLES / HUBS

- 20,000 LB RATING
- HUB PILOTED

SUSPENSION

HUTCH 9700 - 3 SPRING SUSPENSION

TONGUE

14' LENGTH, 8 X 8 X 1/2" SQUARE TUBE, INTEGRAL WITH CHASSIS

ESTIMATED BODY WEIGHT

6,900 LBS

HOIST CYLINDER MOUNTS

- LOWER SHAFT 3 ½"
- UPPER SHAFT 2 ½"

HOIST CYLINDERS

- (2) SINGLE STAGE, DOUBLE ACTING
- LENGTH 77 ½"/ DIAMETER 6" O.D.
- BORE 5 ½"/ STROKE 62 5/8"
- ROD 3" CHROME
- MATERIAL D.O.M. TUBING

REEVING CYLINDERS

- SINGLE STAGE, DOUBLE ACTING
- LENGTH 97 ½"/ DIAMETER 6 ½"
- BORE 6"/ STROKE 83 5/8"
- ROD 3" CHROME
- MATERIAL D.O.M. TUBING

STANDARD SPECIFICATIONS (CONT.)

REAR BUMPER

 REAR BUMPER WITH TAIL, STOP, BACK UP LIGHTS AND MUD FLAPS

HINGE PIN

• 2"

FENDERS

FULL COMPOSITE - MINIMIZER

CABLE PULLEY

9" DIAMETER WITH BRONZE BUSHINGS

ROLLERS

(3) ON EACH RAIL, 4 1/2" DIAMETER WITH ZERK FITTINGS

CABLE

STANDARD 7/8" X 75' WITH PEAR RING END

ROLL-OFF OPTIONS

FENDERS

- 1/4 STEEL (PAINTED)
- 1/4 STAINLESS (POLISHED)
- FULL STEEL (PAINTED)
- FULL ALUMINUM (POLISHED)

TOOL BOX

- ALUMINUM T-HANDLE
- TARP/CARRY BASKET ATTATACHED TO TOOL BOX

TIE DOWNS

- RACHET, HOOK FOR TIE DOWN AT REAR
- DOT CHAINS

TOOL BOX

STEEL LOCKABLE 36" CURBSIDE

CONTROLS

AIR / HYDRAULIC TWIN-STICK

CONTROL VALVE

COMMERCIAL A-35

OPERATING PRESSURE

1,800 PSI

PAINT

GLOSSY BLACK

RAIL OPTIONS

- ADDITIONAL ROLLERS
- ANGLE BETWEEN ROLLERS
- CHANNEL RAILS

FIRE PROTECTION

20LB FIRE EXTINGUISHER MOUNTED EXTERNALLY

LIGHTING

LED LIGHTING PACKAGE

TARPING SYSTEM

 PIONEER COVERALL RP4500SARG (OTHER MODELS AVAILABLE UPON REQUEST)