



ROLL-OFF PULL TRAILER MODEL AMTTR-24 STANDARD SPECIFICATIONS

THE FOLLOWING SPECIFICATIONS ARE FOR A STANDARD ROLL – OFF PULL TYPE TRAILER TO BE PULLED BY A STANDARD ROLL – OFF UNIT.

PULL TRAILER SPECIFICATIONS

TYPE

- REEVING SYSTEM

RAIL SIZE

- 10" X 4" X 3/8" RECTANGULAR TUBING 26" WIDTH – 34"

CONTAINER CAPACITY

- UP TO 24" (LARGER AVAILABLE)

WHEELBASE

- 236"

SUSPENSION

- 20,000 LBS THREE LEAF EACH AXLE

AXLES

- 23,000 LBS K-B, 5" O.D. 1/2" WALL TUBULAR

BRAKES

- FRONT – 6 1/2" X 6" AIR "S" CAM WITH MANUAL SLACK ADJUSTERS
- REAR – SAME AS FRONT WITH SPRING BRAKE
- ANTI-LOCK BRAKE SYSTEM

LIGHTING

LED LIGHT PACKAGE

HUBS

- INBOARD TYPE 10 STUD (3/4")

TONGUE

- AIR LIFT LOW MOUNT

CABLE PULLEY

- 9" DIAMETER WITH BRONZE BUSHING

ROLLERS

- (3) EACH RAIL 4 1/2" DIAMETER WITH ZERK FITTINGS

FENDERS

- QUARTER FENDERS EACH WHEEL

TIRES & WHEELS

- 11R22.5 TIRES ON 22.5 X 8.25 STEEL HUB PILOT WHEELS (ADVISE COLOR)

OPTIONS

- ALUMINUM WHEELS

HYDRAULIC COMPONENTS

REEVING CYLINDERS

- SINGLE STAGE, DOUBLE ACTING
- LENGTH – 97 ½”
- DIAMETER – 4 ½”
- BORE – 4”
- STROKE – 84”
- ROD – 2 ½” CHROME PLATE
- MATERIAL – D.O.M. TUBING

MISCELLANEOUS

REAR BUMPER

- REAR BUMPER WITH TAIL, STOP, BACKUP LIGHTS AND MUD FLAPS

PAINT

- GLOSSY BLACK

ESTIMATED WEIGHT

- 8,500 LBS